



VALVE ID TAGS SPECIFICATION GUIDE



GPH's Valve Id Tags are manufactured in two sizes and in industry standard colors. We keep a large inventory of the stock alpha-numeric options (A1-A99) and have quick turnaround on all custom requirements.

Quick And Permanent Installation

Slip a valve wire (up to 12 guage) through the hole in the tag to easily identify the zone number, designed to use a 18-8 stainless steel screw (not included) to attach the tag to the top of a valve box, or zip tie our ID Tag's to a back-flow preventer for a quick permanent installation.

Engineering Grade For Use In The Toughest Applications

GPH's valve ID Tags are manufactured from an engineering grade UV stabilized Desopan material and are individually hot-stamped for maximum contrast and visibility. They require no maintenance and are designed to be a consistent identification point for all applications. They will remain pliable and visible in the harshest above or below ground applications.

Special ID Or Custom Branding Available

We can work with your design to customize either the standard or Maxi Size tags. Have your message and contact info built into the irrigation system. Our purple Maxi size tags are industry standard for marking systems using Recycled/ Reclaimed water. Style number GRC005 is in English and style number GRC006 is bilingual. A sampling of our current special legends and logos is listed on the following pages. Additionally, tags are available in a variety of colors, to conform to both locally developed standards, as well as APWA and AWWA national standards.

Standard Specification

Identification Tags provided will be manufactured from UV stabilized Behr Desopan engineering grade plastic, incorporating an integral attachment neck and reinforced attachment hole that shall accommodate a 18-8 screw head. GPH ID Tags shall be capable of withstanding at least 180 lbs. of pull out resistance. The STANDARD Identification Tag shall be approximately 2.25" x 2.75" and the MAXI Identification Tag shall be approximately 3" x 4". All stamped identification shall withstand outdoor and submerged usage. The standard alpha-numeric designations shall incorporate alpha-numeric lettering 1.125" in height. Special lettering, designations or stampings will be the maximum size available. The identification tag shall be manufactured by GPH Irrigation.